



• Hydraulic Data

DN (mm)	Kv (m ³ /h)	Cv (l/s)
600	5940	1650
700	6293	1748
800	6922	1923
900	11520*	3200*
1000	12600*	3500*
1200	13680*	3800*

• Technical Data

* Calculated

DN (mm)	L (mm)	L max. (mm)	F (mm)	H (mm)	H1 PN 10-16 (mm)	H1 PN 25 (mm)	H1 PN 40 (mm)	Hm (mm)	A (mm)	B (mm)	Weight (kg)
600	1450	1450	1230	1310	430	430	-	1685	700	650	1950
700	1650	1650	1230	1310	465	490	500	1685	700	650	2100
800	1850	1850	1230	1310	543	550	570	1685	700	650	2350
900	1930	2050	1680	1985	570	600	630	2160	1100	900	5200*
1000	1930	2250	1680	1985	630	660	680	2160	1100	900	5500*
1200	2400	2500	1680	1985	745	770	790	2160	1100	900	5800*

L : Standard CLA-VAL length. L max : according to ISO 5752

The Kv or Cv = m³/h or l/s @ 100 kPa (1 bar) head loss with 15° C water (valve totally open).

CLA-VAL

Switzerland

TEL : +41 (0) 21 643 1555

FAX : +41 (0) 21 643 1550

Web : www.cla-val.ch

E-mail : cla-val@cla-val.ch

© Copyright CLA-VAL CO - USA

NUM.	000125DE
REV.	E 06/06
QUA.	HvB 06/06