



Cla-Val Model 750-SP

Pressure relief valve with Standpipe connections

The Cla-Val model 750-SP is a lightweight and compact pressure relief valve designed to relieve potentially damaging pressures within a pipe. The valve is equipped with a male standpipe adapter fitted to the inlet and female standpipe adapter fitted to the outlet and includes a quick release coupling for a pressure gauge. As inlet pressure begins to exceed the pre-set pressure, the valve will open and modulate to relieve line pressure and keep it below the set point maximum.

- Re-seats drip tight within 5% of its set pressure
- Rugged and lightweight 316L stainless steel body
- High discharge capacity
- Simple two piece construction
- Stable operation across entire flow range
- Quick release coupling for pressure gauge



Standpipe shown for illustration purposes only and is **not included**

Typical applications

- Relieves potential excess line pressure during PRV shut-off's.
- Relieves excess pressure during pump start when for example a reservoir or tank Needs to be bypassed.

Discharge capacity: 15 l/s (with a 1 bar differential pressure)
Pressure rating: 48 bar
Adjustment ranges: 0.1 - 6.0 bar (standard)
1.4 - 14.0 bar
7.0 - 21.0 bar

CLA-VAL UK Limited

Dainton House, Goods Station Road, Tunbridge Wells, Kent TN1 2DH
Tel: (01892) 514400 Fax: (01892) 543423
Email: info@cla-val.co.uk

