



STANDARD EQUIPMENT

| No | Description | Qty | Type |
|----|---|-----|-------------|
| 1 | MAIN VALVE HYTROL AE/GE/NGE | 1 | 100-01 |
| 2 | ISOLATION BALL VALVE | 3 | RB-117 |
| 3 | STRAINER WITH INCORPORATED ORIFICE | 1 | X44-A |
| 4A | ONE-WAY FLOW CONTROL (OPENING SPEED) | 1 | CV |
| 4B | ONE-WAY FLOW CONTROL (CLOSING SPEED) | 1 | CV |
| 5 | POSITIONING MOTORIZED PRESSURE REDUCING CONTROL | 1 | CRD-34 |
| 6 | ELECTRONIC ADVANCED CONTROLLER | 1 | D22 |
| 7 | INSERTION FLOWMETER | 1 | e-Flowmeter |

OPTIONAL FEATURES

| No | Description | Qty | Type |
|----|---------------------------|-----|--------------|
| P9 | PRESSURE REDUCING CONTROL | 1 | CRD + RB-117 |

NOTES

AE/GE : DN 32 - DN 400 / NGE : DN 50 - DN 600
 RB-117 (2D), (2E), (2F), (2G) if option (P9)
 Recommended ValvApps: D22-POUT-DRV.01
 Standard wiring schematic: D22-17-0001

OPTIONAL FEATURES : _____
 NOT FURNISHED BY CLA-VAL : _____