



### ► Technical Data:

	DN 32	DN 40	DN 50	DN 65	DN 80	DN 100	DN 150	DN 200	DN 250	DN 300	DN 400
Flanged (mm)	DN 32	DN 40	DN 50	DN 65	DN 80	DN 100	DN 150	DN 200	DN 250	DN 300	DN 400
Screwed (in)	1 1/4"	1 1/2"	2"	2 1/2"	3"	-	-	-	-	-	-
L	215	215	254	280	305	381	508	645	756	864	1051
L1	184.5	184.5	238	280	318	-	-	-	-	-	-
F	145	145	170	205	235	295	400	510	600	712	900
H	191	191	215	245	260	345	415	495	595	695	850
H1 (PN 10-16)	-	75	82.5	93	100	110	142.5	170	-	-	-
H1 (PN 25)	-	75	82.5	93	100	117.5	150	180	-	-	-
H2	-	-	-	-	-	-	-	-	236	274	395
Hm	252	252	285	320	345	450	540	645	780	905	1120
A	150	150	150	165	203	216	230	285	330	370	475
B	100	100	100	115	127	152	205	260	305	362	450
øC	-	-	47	60	60	82	82	82	82	-	-
Weight (Kg)	13	13	20	25	30	50	95	170	310	470	970

### ► Hydraulic Data:

	DN 32	DN 40	DN 50	DN 65	DN 80	DN 100	DN 150	DN 200	DN 250	DN 300	DN 400
Flanged (mm)	DN 32	DN 40	DN 50	DN 65	DN 80	DN 100	DN 150	DN 200	DN 250	DN 300	DN 400
Screwed (in)	1 1/4"	1 1/2"	2"	2 1/2"	3"	-	-	-	-	-	-
Kv (m <sup>3</sup> /h)	26	28	47	72	101	173	400	666	1076	1490	2542
Cv (l/s)	7	8	13	20	28	48	111	185	299	414	706

Kv or Cv = m<sup>3</sup>/h or l/s @ 100kPa (1 bar) head loss with 15°C water (valve totally open).